

SAFETY DATA SHEET JUICE - N CUT

According to the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice, 2021.

SECTION 1: Identification: Product identifier and chemical identity	
Product identifier	
Product name	JUICE - N CUT
Product No.	JPNCUT1L
Relevant identified uses of the s	ubstance or mixture and uses advised against
Application	Car maintenance product Polish.
Uses advised against	For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.
Supplier	Sydney Automotive Paint and Equipment Pty Ltd Unit A3, 366 Edgar Street Condell Park NSW 2200 Australia Tel: +61 2 9772 9000 Email: reception@sape.com.au www.sape.com.au
NZ Distributor	Resene Automotive & Light Industrial 4 Te Apunga Place Sylvia Park Auckland NZ 1641 Tel: +64 9 259 2738 www.resene.co.nz
Emergency Information	
Emergency telephone	NZ Poison Information Centre 0800 764 766 or +64 3 479 7248
General medical information	+61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)
Transport information	+61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

SECTION 2: Hazard(s) identification

Classification of the substance or mixture		
Physical hazards	Flam. Liq. 4 - H227	
Health hazards	Not Classified	

JUICE - N CUT

Environmental hazards	Not Classified
Label elements	
Signal word	WARNING
Hazard statements	H227 Combustible liquid.
Precautionary statements	P264 Wash skin thoroughly after handling. P280 Wear protective gloves. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention.
Supplemental label information	AUH066 Repeated exposure may cause skin dryness or cracking.

Other hazards

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

SECTION 3: Composition and information on ingredients	
Mixtures	
Aluminium oxide	30<60%
CAS number: 1344-28-1	
Substance with a Community workplace exposure limit.	
Classification	
Not Classified	
Distillates (petroleum), hydro- treated light	20<30%
CAS number: 64742-47-8	
Classification	
Flam. Liq. 4 - H227	
Asp. Tox. 1 - H304	
White Mineral Oil (Petroleum)	10<15%
CAS number: 8042-47-5	
Classification	
Asp. Tox. 1 - H304	
Aluminium Oxide	3<5%
CAS number: 1344-28-1	5.570
Substance with a Community workplace exposure limit.	
Classification	
Not Classified	

JUICE - N CUT

BRONOPOL (INN)	0.01<0.1%
CAS number: 52-51-7	
M factor (Acute) = 10	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	

Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335 Aquatic Acute 1 - H400 Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measur	es
Description of first aid measur	es
General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin Contact	Remove affected person from source of contamination. Rinse immediately with plenty of water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.
Most important symptoms and effects, both acute and delayed	
General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.
Indication of any immediate medical attention and special treatment needed	
Notes for the doctor	Treat symptomatically.
Specific treatments	No special treatment required.
SECTION 5: Firefighting measures	

Extinguishing media

Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Special hazards arising from th	e substance or mixture
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
Advice for firefighters	
Protective actions during firefighting	Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.
SECTION 6: Accidental release	e measures
Personal precautions, protectiv	e equipment and emergency procedures
Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage.
Environmental precautions	
Environmental precautions	Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).
Methods and material for conta	inment and cleaning up
Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Reuse or recycle products wherever possible. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Reference to other sections	
Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13.
SECTION 7: Handling and stora	age, including how the chemical may be safely used
Precautions for safe handling	

Precautions for safe handling

Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists.
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.
Conditions for safe storage, in	cluding any incompatibilities
Storage precautions	Store away from incompatible materials (see Section 10). Store in accordance with local regulations.
Storage class	Unspecified storage.
Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.
SECTION 8: Exposure control	s and personal protection
<u>Control parameters</u> <u>Occupational exposure limits</u> Aluminium oxide	
Long-term exposure limit (8-h Long-term exposure limit (8-h	
Aluminium Oxide	
Long-term exposure limit (8-h Long-term exposure limit (8-h	
	White Mineral Oil (Petroleum) (CAS: 8042-47-5)
Ingredient comn	nents No exposure limits known for ingredient(s).
Exposure controls	
Protective equipment	
Appropriate engineering controls	Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. The following protection should be worn: Chemical splash goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.
Environmental exposure controls	Not regarded as dangerous for the environment.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties	
Appearance	Viscous liquid.
Colour	Pink.
Odour	Cherry.
Odour threshold	Not available.
рН	Not applicable.
Melting point	~ 0°C
Initial boiling point and range	e> 100°C @ 760 mm Hg
Flash point	~ 77°C Closed cup.
Evaporation rate	Not available.
Flammability Limit - Lower(%)	Not available.
Other flammability	This product does not sustain combustion, according to the sustained combustibility test L.2, Part III, section 32 of the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria.
Vapour pressure	> 0.04 kPa @ 20°C
Vapour density	Not available.
Relative density	~ 1.380 @ (20°C)°C
Solubility(ies)	Slightly soluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Kinematic viscosity > 20.5 mm²/s.
Oxidising properties	Not applicable.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.
Valatile organic compound	This product contains a maximum VOC content of 281 allitro

Volatile organic compound This product contains a maximum VOC content of 281 g/litre.

SECTION 10: Stability and reactivity		
Reactivity	See the other subsections of this section for further details.	
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.	
Possibility of hazardous reactions	No potentially hazardous reactions known.	
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.	
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.	
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.	
SECTION 11: Toxicological in	formation	
Information on toxicological ef	fects	
Toxicological effects	Not regarded as a health hazard under current legislation.	
<u>Acute toxicity - oral</u> Notes (oral LD₅₀)	Based on available data the classification criteria are not met.	
<u>Acute toxicity - dermal</u> Notes (dermal LD50)	Based on available data the classification criteria are not met.	
Acute toxicity - inhalation Notes (inhalation LC50)	Based on available data the classification criteria are not met.	
Skin corrosion/irritation Animal data	Repeated exposure may cause skin dryness or cracking.	
Serious eye damage/irritation Serious eye damage/irritation Based on available data the classification criteria are not met.		
Respiratory sensitisation Respiratory sensitisation	Based on available data the classification criteria are not met.	
Skin sensitisation Skin sensitisation	Based on available data the classification criteria are not met.	
<u>Germ cell mutagenicity</u> Genotoxicity - in vitro	Based on available data the classification criteria are not met.	
<u>Carcinogenicity</u> Carcinogenicity	Based on available data the classification criteria are not met.	
IARC carcinogenicity	None of the ingredients are listed or exempt.	
<u>Reproductive toxicity</u> Reproductive toxicity - ferti	lity Based on available data the classification criteria are not met.	
Reproductive toxicity - development	Based on available data the classification criteria are not met.	

Specific target organ toxicity - single exposure

STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
Specific target organ toxicity	- repeated exposure
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.
General information	No specific health hazards known. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin Contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.
SECTION 12: Ecological infor	mation
Ecotoxicity	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.
Toxicity	Based on available data the classification criteria are not met.
Persistence and degradabilit	Σχ.
Persistence and degradabilit	ty The degradability of the product is not known.
Bioaccumulative potential	
Bioaccumulative Potential	No data available on bioaccumulation.
Partition coefficient	Not available.
<u>Mobility in soi</u> l	
Mobility	The product is water-soluble and may spread in water systems. The product is non-volatile.
Other adverse effects	
Other adverse effects	None known.
SECTION 13: Disposal conside	erations
Waste treatment methods	
General information	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.
Disposal methods	Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water authority.

authority.

SECTION 14: Transport information

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADG).

UN number

Not applicable.

UN proper shipping name

Not applicable.

Transport hazard class(es)

No transport warning sign required.

Packing group

Not applicable.

Environmental hazards

Environmentally hazardous substance/marine pollutant No.

Special precautions for user

Not applicable.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Schedule (SUSMP)

No Poison Schedule number allocated

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Australia - AIIC

All the ingredients are listed or exempt.

SECTION 16: Any other relevant information

Abbreviations and acronyms used in the safety data sheet	ADG: Australian dangerous goods code
	AllC: Australian Inventory of Industrial Chemicals IATA: International air transport association.
	ICAO: Technical instructions for the safe transport of dangerous goods by air.
	IMDG: International maritime dangerous goods.
	CAS: Chemical abstracts service.
	ATE: Acute toxicity estimate.
	LC_{50} : Lethal concentration to 50 % of a test population.
	LD ₅₀ : Lethal dose to 50% of a test population (median lethal dose).
	EC₅₀: 50% of maximal effective concentration.
	PBT: Persistent, bioaccumulative and toxic substance.
	vPvB: Very persistent and very bioaccumulative.

General information	This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain. www.autosmartinternational.com rbutler@autosmart.co.uk Tel +44 (0)1543 481616
Revision date	13/03/2023
Revision	5_AUS
Supersedes date	06/07/2022
SDS No.	22090
SDS status	Approved.
Hazard statements in full	 H227 Combustible liquid. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.