

Status:	Ok
Approval:	06.08.2021

Classification	
	Public series
Product type:	Bonded abrasives
Main industries:	General Fabrication
Further industries:	Trucks Rail Marine Bus Wind Power Windows and Doors Containers Casting and Forging Turbines Knives, cutlery Tools Shipbuilding Machinery, equipment Stamped and Shaped Parts Tubes and Profiles

Product profile	
Grit type:	Aluminium oxide
Grit range (total):	FEPA F / ISO 8486
Backing:	
Coating:	
Bonding:	Resin over resinGlass fibre
Special coating:	
Equipment:	

Properties		Technology
Removal rate:	9 - very high	- X-LOCK
Lifetime:	9 - very long	
Finishing:		
Flexibility:	1 - very rigid	
Contact pressure:	7 - strong	

Advantages	
General Fabrication:	- Aggressive cut - High performance for stock removal - Long lifetime - Comfortable to use with little contact pressure

Applications

General Fabrication:	- Welded seam preparation - Removal of fillet welds - Removing solid material - Deburring
----------------------	--

Material

General Fabrication:	Steel ● steel Steel ○ Unalloyed / low-alloy steel Steel ○ Ferrous metal
----------------------	---

Conversion forms

	Upper conversion	Lower conversion
--	------------------	------------------



Discs	- Grinding discs
-------	------------------

Application

	Superordinate group	Subgroup
	Portable machine sanding	Angle grinder
Cut:		

Details

No suitability for:	
Sanding recommendation:	
Safety recommendation:	Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety - Follow the general EN safety recommendations - Follow the general FEPA safety recommendations - Pay attention to the abrasives safety data sheet (available from sia Abrasives) - Use eye and face protection - Use an effective dust extraction unit or wear a fine dust mask - Use hearing protection

Communication

Claim:	Highly efficient, hard grinding discs for iron and steel
Copy:	The hard grinding discs of the special 8933 siagrind series excel in a variety of metal applications and make for robust and efficient tools thanks to features such as high removal rates at low surface pressure and long life.



Communication			
Image material:	Product Top View (PTV)	Front side:	ID 5043
		Rear side:	ID 5043
	Application image	General Fabrication:	ID 4703
	Product show:		
	Macro shot:		
	Packaging image:		
	Product group image:		

- Main application
- Secondary application