

Article number: 9300

Description: Easy2Check®

EAN: 8714247037898



Colad Easy2Check®

400 ml per can. Used to or on car panels for panel checking during the sanding process. The 'glossy finish' helps detecting any defects or colour deviations. Spray the panel after the sanding process to check repaired surfaces on irregularities. Can also be used for spray sample checks! Spray on a spray sample to create a glossy finish and check if the colour corresponds.

Benefits of Easy2Check®

- Checks repaired surfaces
- Checks for any irregularities while sanding panels
- Detects any defects or colour deviations
- Creates a temporary gloss on either spray cards for color matching
- Reduces costs
- Economize on valuable clearcoat consumption
- Efficient and fast
- Clean and Easy handling
- Evaporates completely after 15-20 minutes. (use compressed air to shorten the evaporation time.)
- Leaves no residue
- Can be used outside the spray cabin / paint preparation room
- Can be used in the bodyshop or paintshop
- Safe to spray on cured plastic filler

Packaging information

Per can of 400 ml

Technical information

- Odor: Odorless
- Residu: Evaporates completely without leaving residue after +/- 15 minutes

Frequently Asked Questions

> How to check for defects or irregularities while sanding?

Sanding / Panel Check: To check straightness of a repaired panel during the sanding process. Simply spray on Colad Easy2Check® to create a temporary gloss and examine the panel for any defects.

> **How to use for color paint matching?**

Spray on base coat Spray Sample [Art.no.9315] to create a temporary gloss. Match the sample with the car. Advisable is to also spray on the object to get the best effect. Repeat this process until the optimal color has been achieved.

> **What does Easy2Check do?**

The 'glossy finish' helps detecting any defects or colour deviations.

> **Can it be sprayed on cured plastic filler?**

Safe to spray on cured plastic filler.

> **Can it effect the cast of colors?**

UV-Blockers in a clear coat can affect the cast of certain colors compared to using Colad Easy2Check®. Advise is to use the appropriate clear coat to confirm for a final check.

Related products



9315

Metal Spray Samples



931901

Magnetic Holder



9319SLEEVE

Spray Sample Sleeve

Certifications



EG 1907/2006

TECHNICAL DATA SHEET



Creation date: 15-12-23

Number of pages: 3



MSDS

Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.