


Always use correct Personal Protective Equipment


C-POWER

Description



C-Power is a high strength industrial cleaning fluid with the addition of citrus as a natural cleaner that is **fully biodegradable**.

Products




Product Type:	Cleaner
Colour:	Clear
Pot Life:	N/A
Induction Time:	N/A
Density:	Approx 1.00 kg/L.
Recommended DFT:	N/A
Theoretical Coverage:	N/A

Properties



VOC:	N/A
Volume Solids:	N/A
Solubility in water:	Soluble
Recoat-ability:	N/A
Dry Time @ 20°C:	
Other properties:	Has a sweet odour


Substrates



Vinyl, Laminates and Flooring. Also used as a vehicle wash to help remove silicon grooming oils etc. Use at 20:1 for this purpose and try a small test area first.

Directions

For Use



C-Power can be used on all hard surfaces and diluted by 100 parts of water depending on surface condition.

Spray

Equipment:



Can be brushed or pressure sprayed on, also feed into water blasters.

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.

Always use correct Personal Protective Equipment**Health & Safety**

Irritant-Avoid contact with eyes or skin. If swallowed, DO NOT induce vomiting. Contact a doctor or a Poisons Information Centre. For further safety information consult the current Safety Data Sheet (SDS).

Transport & Storage

Sizes: 1L, 5L, 20L
Dangerous Goods: 6.1B
UN: 1263
Hazchem: 2Z
Packing Group: II
Shipment name:
Flash point: Above 61°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.