








GMH BLACK

Description

- Nitrocellulose based industrial lacquer
- Can be used as a guide coat

Technical Summary

- Quick drying
- Low gloss
- Good coverage
- Easy to apply
- Ready for use

	Working process	Nitrocellulose lacquer and as a guide coat
	Substrates:	Subframes, beneath mudguards etc.
	Pretreatment / Cleaning:	Clean with Duxone® Wax and Grease Remover
	Application:	Use recommended respirators. Refer to relevant Material Safety Data Sheet (MSDS)
		Ready for use, shake well before use
		1.6 – 1.8 mm 300 – 400 kPa 3 coats = approx. 10 microns
		1.8 – 2.0 mm 300 – 400 kPa 2 – 3 coats = approx. 10 microns
		5 minutes / 20°C between coats
		10 minutes / 20°C

GMH BLACK

TECHNICAL DATA

	Flashpoint:	Approx. -5 °C
	Raw Material:	Nitrocellulose based resins
	Specific Gravity:	0.8 g/L
	Approx. Coverage:	6.5 m ² /L at 10 microns DFT
	Cleaning of Equipment:	Clean after use with Duxone® Acrylic Thinners
	Important Remarks:	For professional use only Notes: 1. As Duxone® GMH Black is a fast drying Nitrocellulose based lacquer, there may be a tendency for this product to bloom or blush in cold weather 2. Not for exterior exposure
<p>This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.</p>		