



Spray Kleen

Description




Spray Kleen is a versatile cleaner designed for a variety of uses around the house, workshop or commercial cleaning (bathroom tiles, shower walls and floors, carpets etc). Spray Kleen will remove smoke stains on ceilings, mould and mildew and can also be used as a laundry pre-soak. It is a completely water soluble, mildly alkaline cleaner that contains a blend of water softening detergents.

Products



Product Type: Concentrate ready for dilution
Colour: Opaque Blue/green
Density: Approx. 1.00 kg/L
Solubility in water: Soluble

Substrates




Spray Kleen is an all purpose cleaner with many household and commercial uses.

Ceramic tiles.
 Floors including linoleum.
 Existing paint work.
 Household appliances.

Please note: For best practise use a small test area first to confirm desired result.

Dilution



Heavily soiled substrate: 10 parts water to 1 part Spray Kleen
 Medium soiled substrate: 20 parts water to 1 part Spray Kleen
 Smoke stains: 20 parts water to 1 part Spray Kleen
 Low soiled substrate: 40 parts water to 1 part Spray Kleen

Directions For Use



Mildew or mould: Spray on and leave for 5-10 minutes. Wipe off with a wet cloth.
 Smoke Stains: Spray or wipe on leaving for 10 minutes. Wipe off with a wet cloth.
 Mud or grime from rubber or plastics on commercial equipment: Spray on and hose off with water.

Please note: For best practise use a small test area first to confirm desired result.

Health & Safety



If swallowed, rinse out with fresh water and contact the Poison Centre or consult a doctor.
 Wear rubber gloves, if you have sensitive skin.
 If contact with solution is made, remove all contaminated clothing and wash body with soap and water.
 If inhaled and breathing becomes difficult, remove to fresh air and keep in rest position. If condition continues seek medical assistance.

If solution gets in eyes, rinse cautiously with water for several minutes. Continue rinsing if eye irritation persists.

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.

Health & Safety cont'd

For further information contact Resene Automotive and Light Industrial Ph 0800 108 008 or NZ National Poison Centre Ph 0800 Poison.



Wear protective clothing and gloves

Transport & Storage



Sizes:	4L, 20L
Dangerous Goods:	3
UN:	UN 1760
Hazchem:	2X
Packing Group:	III
Shipment name:	Non-flammable

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.